



PeakPro Plus Harness With Positioning Belt 5D - Class APE



X Denotes Belt Size :
1 = S
2 = M
3 = L
4 = XL
5 = XXL



ORDERING INFORMATION

Product No.	Model No.	Sizes
V800517X	FBH-70110G-X	S-XXL

TECHNICAL SPECIFICATIONS

- Material: Polyester “peekaboo” webbing, anodized aluminum hardware
- Chest Buckles: Aluminum Stab Lock
- Leg Buckles: Aluminum Stab Lock
- Weight: 3 lb
- Number of Workers: 1
- Class: APE
- Capacity: Combined weight of person, tools, clothing, etc. 130 lbs to 310 lbs (60 kg to 141 kg) as indicated by ANSI Z359.11
- Operating Temperature: -35° C to +35° C

STANDARD COMPLIANCE

- Certified to: CSA Z259.10, and ANSI Z359.11
- Meets or exceeds OSHA standards

COMPONENT COMPATIBILITY

- PeakWorks equipment has been designed for use with PeakWorks approved components or subsystems (full body harnesses, lifelines, rope grabs, connectors, self-retracting lifelines, etc.) or as recommended by a qualified person.
- Warning:** See operating and maintenance instruction manual for details.

Storage: Store in a cool dry place away from chemicals, water, corrosive environments, and sources of heat or spark.

Description and Performance:

The PeakWorks PeakPro Plus harness is a class APE full body harness that provides increased durability and premium comfort. All hardware components are made from high-grade anodized aluminum for corrosion resistance, reduced weight, and improved longevity. Special “peekaboo” webbing is designed to aid in the inspection of the harness. In case of damage or excessive wear, the webbing shows red indicating that the harness should be removed from service. Trauma straps are integrated into the harness and allow a standing position and improved circulation in the legs before rescue. In addition, each harness is fitted with upgraded shoulder and leg pads as well as a comfortable belt.