



Specification & Data Sheet

Contractor Kit

Front



Product No.	Carrying Bag
V8252356	No
V8252357	Yes

ORDERING INFORMATION

Kit Model No. 4456-KIT03S

Description:	Contractor Harness	Shock Pack Lanyard
Style	<ul style="list-style-type: none"> • Class A harness • 5-point adjustable pass thru buckles 	<ul style="list-style-type: none"> • Single leg, tear pack • 2 double locking snap hooks
Materials	<ul style="list-style-type: none"> • Polyester webbing • Steel buckles 	<ul style="list-style-type: none"> • 1" polyester webbing • Steel snap hooks
Standards	<ul style="list-style-type: none"> • OSHA • Certified to ANSI Z359.11 • Certified to CSA Z259.10 	<ul style="list-style-type: none"> • OSHA • Certified to ANSI Z359.13
Size	<ul style="list-style-type: none"> • Universal 	<ul style="list-style-type: none"> • 6' length (1.8 m)
Operating Temperature	<ul style="list-style-type: none"> • -31° F to 95° F (-35°C to 35°C) 	<ul style="list-style-type: none"> • -31°F to 95°F (-35°C to 35°C)
Max Working Load (Combined weight of person, tools)	<ul style="list-style-type: none"> • 130 to 310 lbs. (60 to 141kg) • Single Use Only 	<ul style="list-style-type: none"> • 130 to 310 lbs. (60 to 141kg) • Single Use Only

Back



Description and Performance:

The Peakworks® Contractor Kit includes a Harness and Shock Absorbing Lanyard. The full body harness features 5 points of adjustment for maximum comfort (2 shoulder, 2 leg, 1 chest). Quick connect pass thru buckles, located on the chest and legs, make it easy for donning. All of the Peakworks harnesses include fall indicators for ease of inspection and 2 lanyard parks for easy and safe lanyard storage. The Shock Pack Lanyard is certified to the newest and strict ANSI standards. The Shock Absorbing Lanyard is comprised of "tear webbing" which will significantly limit and reduce the force of a fall on a worker.