



Specification & Data Sheet

Compliance Kit

Back



Product No.	Carrying Bag
V8252366	No
V8252367	Yes

ORDERING INFORMATION

Kit Model No. 4400-BA1CKTS

Description:	Compliance Harness	Permanently Affixed Shock Pack Lanyard
Style	<ul style="list-style-type: none"> • Class A harness • 3-point adjustable pass thru buckles 	<ul style="list-style-type: none"> • Single leg, tear pack • 1 double locking snap hook - permanently attached
Materials	<ul style="list-style-type: none"> • Polyester webbing • Steel buckles 	<ul style="list-style-type: none"> • 1" polyester webbing • Steel snap hook
Standards	<ul style="list-style-type: none"> • OSHA • Certified to ANSI Z359.11 • Certified to CSA Z259.10 	<ul style="list-style-type: none"> • OSHA • Certified to ANSI Z359.13
Size	<ul style="list-style-type: none"> • Universal 	<ul style="list-style-type: none"> • 6' length (1.8 m)
Operating Temperature	<ul style="list-style-type: none"> • -31° F to 95° F (-35°C to 35°C) 	<ul style="list-style-type: none"> • -31°F to 95°F (-35°C to 35°C)
Max Working Load (Combined weight of person, tools)	<ul style="list-style-type: none"> • 130 to 310 lbs. (60 to 141kg) • Single Use Only 	<ul style="list-style-type: none"> • 130 to 310 lbs. (60 to 141kg) • Single Use Only

Front



SureWerx USA Inc.
 Elgin, IL 60123
 Phone: (800) 323-7402
 Fax: (847) 717-8419
 www.surewerx.com/usa

Description and Performance:

The Peakworks® Compliance Kit includes an all-in-one Harness and Shock Absorbing Lanyard. The full body harness features 3 points of adjustment for ultra lightweight comfort. Quick connect pass thru buckles, located on the chest and legs, make it easy for donning. All of the Peakworks harnesses include fall indicators for ease of inspection and 2 lanyard parks for easy and safe lanyard storage. The Shock Absorbing Lanyard is certified to the newest and strict ANSI standards. The Shock Absorbing Lanyard is permanently attached to the rear dorsal D-Ring for simplicity. The Lanyard is comprised of "tear webbing" which will significantly limit and reduce the force of a fall on a worker.